

# OP1500 Single fiber SFP

OP1500 Single fiber SFP supports transparent transmission in Single-fiber of bi-directional data. It is hot-pluggable and suitable for fast Ethernet communication.

## Feature

- ★ Two LC optical connectors, support hot-swap
- ★ Complied with ITU-TG957, G958, MSA
- ★ Single 3.3V power supply
- ★ Work wavelength:1310/1490/1550
- ★ Generally compatible
- ★ Metal shell to shield from EMI
- ★ Stable performance



## Order information

Model	Rate (bps)	Wavelength (nm)	Mode	Distance	TX (dbm)	RX (dbm)	Connector	Temperature
OP1500S-L20-T13	155M	1310/1550	SM	20km	-14~-8	<-32	LC	0~70
OP1500S-L20-T15	155M	1550/1310	SM	20km	-14~-8	<-32	LC	0~70
OP1500S-L60-T13	155M	1310/1550	SM	60km	-5~0	<-34	LC	0~70
OP1500S-L60-T15	155M	1550/1310	SM	60km	-5~0	<-34	LC	0~70
OP1500S-L100-T49	155M	1490/1550	SM	100km	-5~1	<-34	LC	0~70
OP1500S-L100-T55	155M	1550/1490	SM	100km	-5~1	<-34	LC	0~70