

OP1600 single fiber SFP

OP1600 single fiber SFP supports transparent transmission in single-fiber of bi-directional data. It is hot-pluggable and suitable for fast Ethernet communication.

Feature

- ★ LC optical connectors, support hot-swap
- ★ Complied with ITU-TG957, G958, MSA
- ★ Single 3.3V power supply
- ★ Work wavelength: 1310/1490/1550
- ★ Generally compatible
- ★ Metal shell to shield from EMI
- ★ Stable performance



Order information

Model	Rate (bps)	Wavelength (nm)	Mode	Distance	TX (dbm)	RX (dbm)	Connector	Temperature
OP1600S-L10-T13	1250M	1310/1550	SM	10km	-9~-3	<-22	LC	0~70
OP1600S-L10-T15	1250M	1550/1310	SM	10km	-9~-3	<-22	LC	0~70
OP1600S-L20-T13	1250M	1310/1550	SM	20km	-7~0	<-22	LC	0~70
OP1600S-L20-T15	1250M	1550/1310	SM	20km	-7~0	<-22	LC	0~70
OP1600S-L80-T49	1250M	1490/1550	SM	80km	-3~3	<-23	LC	0~70
OP1600S-L80-T55	1250M	1550/1490	SM	80km	-3~3	<-23	LC	0~70