

FC622F ATM Single/Multi-Mode Converters

Overview

HiOSO Ficom FC622F series ATM single/multi-mode converters are applied to 622Mbps ATM, SDH and 100Mbps fast Ethernet network with hybrid wiring of single-mode and multi-mode fibers. Ficom FC622F series ATM single/multi-mode converters can implement mutual conversion between single-mode and multi-mode 1310nm wavelength as well as mutual conversion among 850nm, 1310nm and 1550nm wavelength, and implement signal trunking, so that the transmission distance of signal in multi-mode fiber can be extended longer. FC622F supports transmission in dual-fiber multi-mode、 dual-fiber single-mode and single-fiber single-mode fibers.

Features

- Protocols supported: 622Mbps ATM/SDH;
- Capable of mutual conversion between 1310nm multi-mode fiber and 1310nm/1550nm single-mode fiber;
- Supporting direct and transparent transmission of packets in different length;
- Low power consumption, low heat and capable of stable operation for a long period time;
- Supporting multiple types of fiber ports, such as dual-fiber multi-mode、 dual-fiber single-mode and single-fiber single-mode, to satisfy the extended requirements of users.

Application

622MbpsATM/SDH optical network with long-distance transmission

Pictures



Technical Specifications

Parameters	Specifications
Access mode	622Mbps
Standard	622Mbps ATM/SDH
Wavelength	850nm/1310nm/1550nm
Transmission distance	Dual-fiber multi-mode: 2Km; Dual-fiber single-mode: 10/20/40/60/80/100/120Km
Port	One multi-mode fiber port: Multi-mode – SC (fiber size: 50,62.5/125μm) One single-mode fiber port: single-mode SC fiber port (fiber size: 9/125μm)
Conversion mode	Medium conversion
Delay	< 0.3μs
Bit error rate	<1/1000000000
MTBF	100,000 hours
LED	POWER (power) SM LINK (single-mode fiber link) MM LINK (multi-mode fiber link)
Power	AC220V 0.3A/DC-48V 0.5A

Address: 6th Floor, 12th Building, Wangtang Industrial Zone, Xingao Road, Xili, Nanshan District, Shenzhen
Tel: 86 755-8312-8820 **Fax:** 86 755-8315-1488 755-8312-8484

Email: sale1@haishuo.com may_haishuo@yahoo.com **Web:** www.haishuo.com

Power consumption	3.5W
Operating temperature	-10~55°C
Operating humidity	5%~90%
Storage temperature	-40~70°C
Storage humidity	5%~90% (non-condensing)
Dimensions	26mm(H)*85mm(W)*135mm(D) (height * width * depth) (built-in power) 110mm(H)*22mm(W)*81mm(D) (height * width * depth) (module card)

Order Information

Model	Rate (Mbps)	Conversion Mode	Working Wavelength (nm)	Multi-mode Transmission Distance	Single-mode Transmission Distance	Fiber Interface	Power
FC622FP-M13SC2-S13SC25/40	622	Multi-mode to single-mode	1310-1310	2km	25/40km	SC	AC220V/ DC-48V
FC622FP-M13SC2-S15SC60/80/100	622	Multi-mode to single-mode	1310-1550	2km	60/80/100km	SC	AC220V/ DC-48V
FC622FC-M13SC2-S13SC25/40	622	Multi-mode to single-mode	1310-1310	2km	25/40km	SC	Module card DC5V
FC155FC-M13SC2-S15SC60/80/100	622	Multi-mode to single-mode	1310-1550	2km	60/80/100km	SC	Module card DC5V